



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>7</sup> : B01D 39/20, F01N 3/02	AI	(11) International Publication Number: WO 00/01463 (43) International Publication Date: 13 January 2000 (13.01.00)
--	----	---

(21) International Application Number: PCT/DK99/00390

(22) International Filing Date: 7 July 1999 (07.07.99)

(30) Priority Data:  
PA 1998 00902 7 July 1998 (07.07.98) DK(71) Applicant (for all designated States except US): SILENTOR  
NOTOX A/S [DK/DK]; Baldersbuen 22, DK-2640 Hede-  
husene (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): STOBRE, Per [DK/DK];  
Prinsesse Maries Allé 17, DK-1908 Frederiksberg (DK).  
HØJ, Jakob, Weiland [DK/DK]; Ellegårdsvænget 16,  
DK-2820 Gentofte (DK).(74) Agent: PLOUGMANN, VINGTOFT & PARTNERS A/S;  
Sankt Annæ Plads 11, P.O. Box 3007, DK-1021 Copen-  
hagen K (DK).(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU,  
AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ  
(Utility model), DE, DE (Utility model), DK, DK (Utility  
model), EE, EE (Utility model), ES, FI, FI (Utility model),  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG,  
MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE,  
SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA,  
UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM,  
KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM,  
AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT,  
BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU,  
MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GW, ML, MR, NE, SN, TD, TG).

## Published

*With international search report.**Before the expiration of the time limit for amending the  
claims and to be republished in the event of the receipt of  
amendments.*

(54) Title: DIESEL EXHAUST GAS FILTER

## (57) Abstract

A filter device for filtering soot particles from diesel engine exhaust gases comprises a casing, a shaped porous filter body, preferably of silicon carbide, SiC, such as a honeycomb structure wall flow filter body made from SiC particles. A membrane made from particles and/or fibres and having a smaller pore size than the filter body is applied on the gas outlet side surfaces of the filter body, and a catalytically active coating is applied on, and in the interior of, the filter body, e.g., on a wash coating. The design of the filter body with the small pore size membrane applied to outlet surfaces allows soot particles to travel into the interior of the filter which has relatively large pores and where they are removed by decomposition by contact with the catalyst deposited in the filter body. Due to the small pore size of the membrane on the outlet side, the filter is able to remove very small soot particles, and due to the large active area where an oxidation catalyst and the trapped soot interact, the temperature at which the soot is decomposed is relatively low.